



# SPORTRAK TIRE TBR PATTERN GUIDE 2021







## SP301



- ◇.Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇.4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	13.6	2725/2575	875
225/70R19.5	6.75	14PR	128/126	M	13	1800/1700	760
245/70R19.5	7.50	16PR	135/133	L	13	2180/2060	830
265/70R19.5	7.50	16PR	143/141	J	13	2727/2575	850
295/60R22.5	9.00	18PR	150/147	K	16	3350/3075	900
315/60R22.5	9.75	18PR	151/148	L	14.5	3650/3350	900
315/70R22.5	9.00	18PR	151/148	M	14.5	3450/3150	830



## SP302



- ◇.Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇.4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
8R17.5	6.00	12PR	122/120	J	13	1500/1400	760
8.5R17.5	6.00	12PR	121/120	M	11.5	1450/1400	625
215/75R17.5	6.00	16PR	135/133	L	13	2180/2060	860
235/75R17.5	6.75	16PR	143/141	L	13	2725/2527	860
255/70R22.5	7.50	16PR	140/137	N	10.5	2500/2300	830
275/70R22.5	8.25	16PR	148/145	M	13	3150/2900	900



## SP303



- ◇.Used for driving wheel
- ◇.Widen tread design, can increase the contact area of tread and ground grasping capacity
- ◇.Transverse pattern design, supply good self-cleaning

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
275/70R22.5	8.25	16PR	148/145	K	20.5	3150/2900	900
295/60R22.5	9.00	18PR	150/147	K	19	3350/3075	900
315/70R22.5	9.00	18PR	151/148	M	19	3450/3150	830
315/80R22.5	9.00	20PR	157/154	L	20.5	4125/3750	900



## SP304



- ◇.Vertical deep groove design can provide excellent driving and braking force.
- ◇.The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇.Can be used for mixed road condition.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12R22.5	9.0	18PR	152/149	G	20.5	3550/3250	930
295/80R22.5	9.00	18PR	152/149	G	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	J	20.5	4125/3750	900
315/80R22.5	9.00	20PR	157/154	J	23.5	4125/3750	900



## SP305



- ◇.Suitable for driving wheel position of middle/long distance trucks on better road conditions.
- ◇.Directional mixed pattern design provides extremely good traction and prevents hydroplaning.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
215/75R17.5	6.00	16PR	135/133	J	13.6	2180/2060	865
225/70R19.5	6.75	14PR	128/126	L	15	1800/1700	760
235/75R17.5	6.75	18PR	143/141	J	13.6	2725/2575	865
245/70R19.5	7.50	14PR	133/131	L	15	2060/1950	760
265/70R19.5	7.50	16PR	143/141	J	17.5	2727/2575	850
275/80R22.5	8.25	18PR	149/146	M	17.4	3250/3000	900



## SP306




- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
425/65R22.5	13.00	20PR	165	K	18	5150	830
445/65R22.5	13.00	20PR	168	L	18	5600	830





## SP307



- ◇.Suitable for all position of trucks running on/off road.
- ◇.High traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
14.00R20	10.00	20PR	164/161	J	20	4625/4250	690
7.50R16LT	6.00G	8 PR	122/118	M	15	1500/1320	770



## SP310



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	12PR	110/105	M	9.5	1060/925	670
7.00R16LT	5.5F	14PR	118/114	M	11	1320/1180	770



## SP308



- ◇.Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions
- ◇.4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9R22.5	6.75	14PR	136/134	L	14.5	2240/2120	760
10R22.5	7.50	16PR	144/142	M	15	2800/2650	790



## SP311



- ◇.Used for driving wheel
- ◇.Widen tread design, can increase the contact area of tread and ground grasping capacity
- ◇.Transverse pattern design, supply good self-cleaning

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
215/75R17.5	6.00	18PR	135/133	J	12.5	2180/2060	850



## SP309



- ◇.Suitable for all position of trucks running on/off road.
- ◇.High traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
365/80R20	10.00	16PR	160	K	20.0	4500	900
395/85R20	10.00	14PR	158	J	25.0	4250	660
14.00R20	10.00	20PR	164/161	J	20.0	5000/4625	790
16.00R20	11.25	22PR	174/171	G	20.5	6700/6150	760
15.5R20	12.00	20PR	173	K110		6500	790
15.00×600R635	500-635	32PR	182	G90		6500	790
550/75R21	440-533		164	G90		5000	660
355/85R20	10.00			K		4350	830
335/85R20	9.00			K		3975	830



## SP312



- ◇.Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions
- ◇.4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
275/80R22.5	8.25	16PR	149/146	L	14.5	3000/2725	830
295/80R22.5	9.00	18PR	152/149	M	14.5	3550/3250	900





## SP313



- ◇.Used for driving wheel
- ◇.For good road and mixed road condition
- ◇.Widen tread design ,can increase tread contact area and ground grasping capacity

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
295/75R22.5	9.00	14PR	144/141	L	23	2800/2575	760



## SP316



- ◇.Optimized internal contour design to improve durability significantly.
- ◇.High abrasion tread compound combined with widened tread width to enhance expected mileage markedly.
- ◇.Four straight mian pattern grooves to provide excellent handling and high-speed performance.
- ◇.Widened tread width to improve driving stability effectively , giving drivers a better sense of driving

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	L	16.5	4125/3750	900



## SP314



- ◇.The four vertical zigzag pattern groove design offers good traction and brake
- ◇.Special shoulder groove design reduce it's temperature
- ◇.Line of the groove takes special structure,which can keep tire clean from the stone effectively

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/55R22.5	12.25	20PR	160	K	15.5	4500	900



## SP317



- ◇.High abrasion tread compound combined with widened tread width to enhance expected mileage markedly
- ◇.Enhanced chafer to avoid early damage
- ◇.Reinforced tyre body and band structure to provide stronger load capacity

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
215/70R17.5	6.0	10PR	118/116	L	11.5	1320/1250	590



## SP315



- ◇.Optimize internal contour design to improve durability significantly.
- ◇.Deepened pattern depth compound combined with widened tread width to enhance expected mileage markedly.
- ◇.Reinforcing blocks between the main pattern blocks to make the force more uniform and reasonable.
- ◇.Widened tread width to improve driving stability effectively , giving drivers a better sense of driving.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/60R22.5	9.8	20PR	153/150	K	22.0	3650/3350	900



## SP328/SP328C/ SP328L/SP328G/ SP328G+



- ◇.Suitable for all wheels
- ◇.Good traction and braking performance
- ◇.Good durability, anti-puncturing
- ◇.Applied to road with good even poor conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.00R16LT	5.5F	14PR	118/114	M	11	1320/1180	770
7.50R16LT	6.00G	16PR	125/121	M	12.6	1650/1450	870
12.00R20	8.5	18PR	154/151	K	16	3750/3450	830
	8.5	20PR	156/153	K	16	4000/3650	900
12.00R24	8.5	20PR	160/157	K	15.5	4500/4125	900
315/80R22.5	9.00	20PR	157/154	K	15	4125/3750	830





## SP335/BYA991



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	12PR	110/105	K	10.5	1060/925	670
7.00R16LT	5.5F	14PR	118/114	K	11.5	1320/1180	770



## SP396



- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



## SP366



- ◇.Drive axle for on/off road conditions
- ◇.Deep and rigid block design for long life and good traction
- ◇.Cut resistance compound

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
6.50R16LT	5.5F	10PR	107/102	L	9.7	975/850	560
7.00R16LT	5.5F	12PR	115/110	M	9.7	1215/1060	670
7.50R16LT	6.0G	14PR	122/118	L	10.5	1500/1320	770



## SP397



- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16.5	4500	900



## SP395



- ◇.New low heat tire shoulder designed to provide excellent high-speed performance
- ◇.Widened tread design effectively increases the wear volume and extends tire life
- ◇.New design of tread provides excellent wear resistance
- ◇.Optimized tread design effectively reduces rolling resistance
- ◇.Special design provide self cleaning function
- ◇.Unique tire shape and strong steel cord structure providing excellent durability performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



## SP398/BYS98



- ◇.Excellent load capacity and high speed capacity
- ◇.Good wear-resistant, high traction power, excellent anti-puncture
- ◇.Suitable for all kinds of road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	17.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	17.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	17.0	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	17.0	4125/3750	900





## SP501/SPX501



- ◇Wide tread cap with reinforced carcass and bead structure design provides tires with outstanding bearing performance.
- ◇The new formula design endows tire with good performance on bad roads
- ◇Big block shoulder pattern design endows excellent grip performance. Open shoulder design greatly reduces the tire production.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
8.25R20	6.5	16PR	139/137	K	15.6	2430/2300	930
10.00R20	7.5	18PR	149/146	K	16.4/16.9	3250/3000	930
11.00R20	8.0	18PR	152/149	K	16.4/16.9	3550/3250	930
12.00R20	8.5	20PR	156/153	K	16.4/16.9	4000/3650	900
325/95R24	9.0	20PR	162/160	K	15.9	4750/4500	850



## SP507



- ◇The special pattern design provides excellent driving and grip on the compound road surface, and reduces the heat generation of tire shoulder.
- ◇Wider driving surface design makes tires more durable. Strengthen the tire ring design, provides the outstanding loading capacity of tires;
- ◇The new formulation design ensures the adaptability of the tires in various pavement environments;

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
325/95R24	9.0	20PR	162/160	K	15.9	4750/4500	850



## SP502



- ◇Reasonable design of pattern distribution, increase the rigidity of tire shoulder and improve the wear resistance
- ◇Wavy groove design of shoulder pattern to restrain clipping
- ◇The optimized design of the tire structure makes the tire stress distribution more reasonable and more suitable for trailer wheel
- ◇Ultra deep pattern design give the tire long wear life .

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00G	16PR	125/121	M	12.6	1650/1450	870
7.50R20	6.0	16PR	133/131	M	14.1	2060/1950	930



## SPX508



- ◇Wide tread cap with reinforced carcass and bead structure design provides tires with outstanding bearing performance.
- ◇Mixed pattern design and special formula ensure excellent use performance on short distance mining roads
- ◇The special pattern block and super deep pattern design provides good driving performance, and it can be used in many kinds of road with longer mileage

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	J	17.9	3250/3000	930
11.00R20	8.0	18PR	152/149	K	17.9	3550/3250	930
12.00R20	8.5	20PR	156/153	J	17.9	4000/3650	900



## SP506



- ◇The ribbed design provides excellent handling and drainage performance; the special shoulder design provides excellent transformation performance
- ◇Adopt high wear-resistant formula to ensure tire wear resistance and improve service life.
- ◇Special band design improves crown rigidity and reduces rolling resistance to meet the requirements of fuel saving and environmental protection

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
275/80R22.5	8.25	18PR	149/146	M	14.6	3250/3000	900
445/65R22.5	13.00	20PR	168	J	19.5	5600	830



## SPX509



- ◇Wide tread cap with reinforced carcass and bead structure design provides tires with outstanding bearing performance.
- ◇Deeper pattern depth design with super wear resistance formula greatly improve shearing resistance performance and puncture resistance performance. More Suitable For hard Mine
- ◇Thickened sidewall design effectively prevents twin tire from clamping the stone
- ◇Special tread pattern groove design can effectively prevent tires from calmping the stone

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	F	22.4	3250/3000	930
11.00R20	8.0	18PR	152/149	F	24.7	3550/3250	930
12.00R20	8.5	18PR	154/151	F	24.7	3750/3450	830
	8.5	20PR	156/153	F	24.7	4000/3650	900





## SP516



- ◇ Vertical pattern design on tread region reduces the lateral sliding, improve the tire operation performance, steering performance and drainage performance
- ◇ The center pattern with Multi incision design effectively reduces the irregular wear of crown and improve the tire grip force
- ◇ Special formula for high heat dissipation and high abrasion resistance compound affords both greater mileage and longer service life.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
265/70R19.5	7.5	16PR	140/138	M	12.6	2500/2360	775



## SP601



- ◇ Specially designed for long distance transportation vehicles on good road conditions, suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- ◇ Comfortable and safer driving experience; longer mileage

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	K	14.5	4125/3750	830



## SP639/BYS695



- ◇ vertical groove pattern design stops anti-slip effectively, and offer excellent handling performance
- ◇ safe and advanced pattern design reduce rolling resistance, and ensure tire fuel economy and high speed performance
- ◇ latest anti-wear formulation ensure excellent anti-wear performance

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
285/75R24.5	8.25	16PR	147/144	M	15.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	M	15.5	3000/2725	830
11R22.5	8.25	16PR	146/143	M	15.5	3000/2725	830
11R24.5	8.25	16PR	149/146	M	15.5	3250/3000	830



## SP831/BYT691



- ◇ Special design for anti-skidding and perfect handling
- ◇ Central tread ensure excellent gripping and reduce rolling resistance
- ◇ Unique technical formula improve the wear-resistance and stability

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
285/75R24.5	8.25	16PR	147/144	M	10.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	M	10.5	3000/2725	830
11R22.5	8.25	16PR	146/143	M	10.5	3000/2725	830
11R24.5	8.25	16PR	149/146	M	10.5	3250/3000	830



## SP832



- ◇ Special design for anti-skidding and perfect handling
- ◇ Central tread ensure excellent gripping and reduce rolling resistance
- ◇ Unique technical formula improve the wear-resistance and stability

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	16PR	146/143	M	10.5	3000/2725	830



## SP901/BS28



- ◇ Suitable for all wheels
- ◇ Good traction and braking performance
- ◇ Good durability, anti-puncturing
- ◇ Suitable for good and bad road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00G	14PR	122/118	K	12.0	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	13.0	1800/1600	770
8.25R20	6.5	16PR	139/137	K	15.5	2430/2300	900
9.00R20	7.0	16PR	144/142	K	15.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	16.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	17.0	3550/3250	930
12.00R20	8.5	20PR	156/153	K	17.5	4000/3650	900
12.00R24	8.5	20PR	160/157	K	17.5	4500/4125	900
11R22.5	8.25	18PR	151/148	K	15.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	15.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	15.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	15.5	3550/3250	900





## SP902/BYD68

- ◇.Used for driving wheel
- ◇.Widen tread design, can increase the contact area of tread and ground grasping capacity
- ◇.Transverse pattern design, supply good self-cleaning



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	18.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	18.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	18.5	4125/3750	900



## SP903



- ◇.Used for driving wheel
- ◇.For good road and mixed road condition
- ◇.Widen tread design ,can increase tread contact area and ground grasping capacity



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
295/75R22.5	9.00	16PR	146/143	L	20.5	3000/2725	830
11R24.5	8.25	16PR	149/146	L	20.5	3250/3000	830
285/75R24.5	8.25	16PR	147/144	L	20.5	3075/2800	830
11R22.5	8.25	16PR	146/143	L	20.5	3000/2725	830



## SP905/BYA685W



- ◇.New tubeless tyre pattern
- ◇.Good traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
385/65R22.5	11.75	20PR	160	K	16	4500	900



## SP907/BS18



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00G	14PR	122/118	K	12.0	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	13.0	1800/1600	770
10.00R20	7.5	18PR	149/146	K	16.0	3250/3000	930
11.00R20	8.0	18PR	152/149	K	16.5	3550/3250	930
12.00R20	8.5	18PR	154/151	K	17.5	3750/3450	830
	8.5	20PR	156/153	K	17.5	4000/3650	900
12.00R24	8.5	20PR	160/157	K	16.0	4500/4125	900



## SP908/BS29



- ◇.With perfect driving performance, used for driving wheel
- ◇.Good ground grasping capability, excellent performance
- ◇.Suitable for rough road and mining road condition



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00H	14PR	122/118	K	15.0	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	16.5	1800/1600	770
8.25R20	6.5	16PR	139/137	K	16.5	2430/2300	930
9.00R20	7.0	16PR	144/142	K	16.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	18.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	19.5	3550/3250	930
12.00R20	8.5	18PR	154/151	K	20.5	3750/3450	830
	8.5	20PR	156/153	K	20.5	4000/3650	900



## SP906



- ◇.Specially designed for long distance transportation vehicles on good road conditions.suitable for all wheel positions of middle and long distance coach,steering wheel position of middle and long distance trucks.
- ◇.Comfortable and safer driving experience;longer mileage



SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	K	14.5	4125/3750	830





## SP909/BY06



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	G	18.0	3250/3000	930
11.00R20	8.0	18PR	152/149	G	20.5	3550/3250	930
12.00R20	8.5	18PR	154/151	G	22.5	3750/3450	830
	8.5	20PR	156/153	G	22.5	4000/3650	900
11R22.5	8.25	18PR	151/148	G	20.5	3450/3150	930
12R22.5	9.0	18PR	152/149	G	20.5	3550/3250	930
13R22.5	9.75	18PR	154/151	G	20.5	3750/3450	830
275/70R22.5	8.25	16PR	148/145	G	20.5	3150/2900	900
295/80R22.5	9.0	18PR	152/149	G	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	G	20.5	4125/3750	900



## SP912/BY35



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.50R16LT	6.00H	14PR	122/118	K	14.5	1500/1320	770
8.25R16LT	6.50H	16PR	128/124	K	15.0	1800/1600	770
8.25R20	6.5	16PR	139/137	K	16.5	2430/2300	930
9.00R20	7.0	16PR	144/142	K	16.5	2800/2650	900
10.00R20	7.5	18PR	149/146	K	18.5	3250/3000	930
11.00R20	8.0	18PR	152/149	K	20.5	3550/3250	930
12.00R20	8.5	18PR	154/151	J	21.5	3750/3450	830
	8.5	20PR	156/153	J	21.5	4000/3650	900
12R22.5	9.00	18PR	152/149	K	22.0	3550/3250	930



## SP910



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	G	20.5	3450/3150	930



## SP913



- ◇.Suitable for driving wheel position of vans on poor road conditions
- ◇.Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance
- ◇.Deeper tread pattern design offers enhanced tire mileage for better economy
- ◇.Reinforced tread block enhances its anti-rupture performance;effectively reducing cracks in groove bottom,thereby resulting in a safer driving experience

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
315/80R22.5	9.00	20PR	157/154	K	17.5	4125/3750	830



## SP911



- ◇.Vertical deep groove design can provide excellent driving and braking force.
- ◇.The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇.Can be used for mixed road condition.
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
10.00R20	7.5	18PR	149/146	G	18.0	3250/3000	930
11.00R20	8.0	18PR	152/149	G	20.5	3550/3250	930
12.00R20	8.5	20PR	156/153	G	22.5	4000/3650	900
11R22.5	8.25	18PR	151/148	G	20.5	3450/3150	930
12R22.5	9.0	18PR	152/149	G	20.5	3550/3250	930
13R22.5	9.75	18PR	154/151	G	20.5	3750/3450	830
295/80R22.5	9.0	18PR	152/149	G	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	G	20.5	4125/3750	900



## SP915/BYD865



- ◇.Vertical deep groove design can provide excellent driving and braking force.
- ◇.The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇.Can be used for mixed road condition.
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.0	18PR	152/149	G	20.5	3550/3250	930
12.00R20	8.5	20PR	156/153	G	22.5	4000/3650	900





## SP916/BYA699C



- ◇.New tubeless tyre pattern
- ◇.Good traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	16.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	16.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	17.5	3750/3450	830



## SP920/BYD68+



- ◇.Excellent driving and braking force, good steering stability on muddy roads.
- ◇.For good roads and mixed road condition.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.5	3450/3150	900
12R22.5	9.00	18PR	152/149	K	18.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	18.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	18.5	4125/3750	900



## SP917



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	20.5	3450/3150	930
12R22.5	9.00	18PR	152/149	K	20.5	3550/3250	930
13R22.5	9.75	18PR	154/151	K	20.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	20.5	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	20.5	4125/3750	900
275/70R22.5	8.25	16PR	148/145	M	20.5	3150/2900	900



## SP921/BYS98+



- ◇.Cross-winding groove tread design can reduce tire rolling resistance.
- ◇.Excellent ride comfort.
- ◇.Anti-skid, steering and excellent stability, low noise.
- ◇.Applicable to good road condition (highway).

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	17.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	17.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830
295/80R22.5	9.00	18PR	152/149	K	17.0	3550/3250	900
315/80R22.5	9.00	20PR	157/154	K	17.0	4125/3750	900



## SP918



- ◇.Vertical deep groove design can provide excellent driving and braking force.
- ◇.The steel cord tire with high density. Good wear-resistant, high traction power. High load capacity.
- ◇.Can be used for mixed road condition.
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12.00R20	8.5	20PR	156/153	G	22.5	4000/3650	900



## SP922



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12.00R24	8.5	20PR	160/157	K	15	4500/4125	900





## SP923



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.0	18PR	152/149	K	15.5	3550/3250	930



## SP925



- ◇.Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇.4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	14.5	2725/2575	875
215/75R17.5	6.00	16PR	127/124	M	14	1750/1600	830
225/80R17.5	6.75	16PR	123/122	L	12.0	1550/1500	750
235/75R17.5	6.75	16PR	132/129	M	16	2000/1850	830
265/70R19.5	7.50	18PR	143/141	J	14.5	2727/2575	850



## SP926



- ◇.Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇.4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	16.0	2725/2575	875
215/75R17.5	6.00	16PR	127/124	M	14	1750/1600	830
225/80R17.5	6.75	16PR	123/122	L	16.0	1550/1500	750
235/75R17.5	6.75	16PR	132/129	M	16	2000/1850	830
265/70R19.5	7.50	18PR	143/141	J	17.5	2727/2575	850



## SP928



- ◇.Suitable for all wheel positions of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- ◇.4 linear grooves design provides excellent directional driving performance and prevents uneven tire wear.

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	14.5	2725/2575	875
265/70R19.5	7.50	18PR	143/141	J	14.5	2727/2575	850



## SP929



- ◇.Drive axle for on/off road conditions
- ◇.Deep and rigid block design for long life and good traction

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
9.5R17.5	6.75	18PR	143/141	J	16.0	2725/2575	875
265/70R19.5	7.50	18PR	143/141	J	17.5	2727/2575	850



## SP935



- ◇.Suitable for all wheels
- ◇.Good traction and braking performance
- ◇.Good durability, anti-puncturing
- ◇.Suitable for good and bad road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11.00R20	8.0	18PR	152/149	K	16.5	3550/3250	930
12.00R20	8.5	20PR	156/153	K	17	4000/3650	900





## SP937



- ◇.Used in all wheel position of coach and van
- ◇.Good ground grasping capacity and sideslip resistance. Low shock when running
- ◇.Both suitable for rough road and highway

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12R22.5	9.00	18PR	152/149	L	16.5	3550/3250	930



## SP981



- ◇.Sturdy tread pattern, suitable for bad road condition
- ◇.Supply excellent traction and driving power
- ◇.Ultra-deep tread depth improve 50% service life
- ◇.Open tire shoulder design, good heat dispersion and self-cleaning
- ◇.Good durability, anti-fatigue properties
- ◇.Suitable for mining /construction bad off road condition

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12.00R24	8.5	20PR	160/157	K	18.5	4500/4125	900
12.00R20	8.5	20PR	156/153	G	22.5	4000/3650	900



## SP962/BYD983



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
7.00R16LT	5.5F	12PR	115/110	K	16	1215/1060	670
	5.5F	14PR	118/114	K	16	1320/1180	770
9.5R17.5	6.75	16PR	133/131	L	15.9	2060/1950	830
	6.75	18PR	142/141	J	15.9	2725/2575	875
12.00R24	8.5	20PR	160/157	K	18.5	4500/4125	900



## SP990



- ◇.Suitable for all wheels
- ◇.Good traction and braking performance
- ◇.Good durability, anti-puncturing
- ◇.Suitable for good and bad road conditions

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
12R22.5	9.00	18PR	152/149	K	15.5	3550/3250	930



## SP965/BYD88



- ◇.Designed for construction and mining road, and short haul
- ◇.Special deep pattern improves the traction and braking performance
- ◇.Reduce heat-producing, enhance the service durability
- ◇.Strengthened steel belts protect the tyre body from puncture
- ◇.Extra deep tread pattern can increase mileage 20%

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	18PR	151/148	K	18.0	3450/3150	930
12R22.5	9.00	18PR	152/149	K	18.0	3550/3250	930
13R22.5	9.75	18PR	154/151	K	18.5	3750/3450	830



## SP997/BYD697



- ◇.Used for driving wheel
- ◇.For good road and mixed road condition
- ◇.Widen tread design ,can increase tread contact area and ground grasping capacity

SIZE	STANDARD RIM	PLY RATING	LOAD INDEX SINGLE/DUAL	SPEED RATE	TREAD DEPTH(mm)	MAX LOAD(kg)	PRESSURE(kpa)
11R22.5	8.25	16PR	146/143	L	20.5	3000/2725	830
11R24.5	8.25	16PR	149/146	L	20.5	3250/3000	830
285/75R24.5	8.25	16PR	147/144	L	20.5	3075/2800	830
295/75R22.5	9.00	16PR	146/143	L	20.5	3000/2725	830